

INTRODUCING
THE WORLD'S FIRST
GREEN RO
WATER PURIFIER.
THAT SAVES
30% OF YOUR
WATER AND RETAINS
ESSENTIAL MINERALS.





To get 1 glass of pure water, conventional RO water purifiers could waste over 5 glasses of water!




Aquaguard Paani ka Doctor is equipped with G.RO.W.TH

G.RO.W.TH stands for Global. Reverse Osmosis. Ultraviolet. Taste Heightener. It is a combination of world-class technologies present individually or collectively in our range of water purifiers.



The all new Aquaguard Enhance Green RO equipped with Global and RO technology of **G.ROLV.TH** saves up to 30% more water than other conventional purifiers during the purification process. Its advanced purification technology also removes disease causing bacteria, virus and other impurities from water while retaining a healthy balance of essential minerals. This Green RO purifier is specially designed for areas where the TDS level in the water is low.

The revolutionary Aquaguard Enhance is equipped with:



Electronic Membrane Life Enhancer - EMLE Prevents scaling of dissolved salts like calcium and magnesium, thereby enhancing the membrane life and improving water flow.



Enhanced Filtration

The particulate filter and clarity cartridge provide depth filtration, ensuring crystal clear water and protection for the membrane.



Enhanced Taste

The special carbon cartridge removes residual organic impurities and revives the original taste of water.



Enhanced Protection

Eliminates tough, new-age contaminants like lead, pesticides and heavy metals from water.



- Trusted by over 10 million mothers
- Certified by 105 leading labs
- Service across 650 towns

ALSO AVAILABLE



Removes excess TDS and makes water pure and sweet.



Equipped to handle extremely high level of TDS.

The Aquaguard Advantage















Technical Specifications*

| Dimensions (W x D x H) in m | m: 316 x 251 x 462 | Input Voltage | : 230 V | AC/50 Hz | Total Iron | : | 0.3 mg/lit. (max.) |
|--|--------------------|-----------------------------------|---------|--------------|------------------------|-------------------|------------------------|
| Net Weight | : 9.2 kg | Input Water Pressure** | : 0.6 – | 2.0 kg/sq.cm | Total Dissolved Solids | s mg/lit.(max.) : | 200 mg/lit.(min.)-2000 |
| Power Rating | : 40 watts | Input Water Temperature: 5 – 45°C | | | | | |
| TDS Reduction: Membrane for Low TDS input water (TDS range 200 to 500 mg/lit): 70% Approx. Membrane for High TDS input water (TDS range 500 to 2000 mg/lit): 90% Approx. | | | | | | | |

Note: If the pressure is higher than the maximum specified, use of the Pressure Reducing Valve is recommended. This accessory is available with our company at an additional cost.

*Specifications are subject to change without prior notice. **Flow rate depends on the input water pressure and condition of the filters.





SMS 'AG<PINCODE>' to 566775



www.aquaguard.in www.facebook.com/EurekaForbes www.twitter.com/EurekaForbes Email: aquaguard@eurekaforbes.com



Scan the QR code to
watch online demo
and lots more.
Download
QR code reader from
www.eurekaforbes.com

